

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
2 June 2005 (02.06.2005)


PCT

(10) International Publication Number
WO 2005/048846 A1

- (51) International Patent Classification⁷: **A61B 6/06** (74) Agent: CHINA PATENT AGENT (H.K.) LTD.; 22/F, Great Eagle Centre, 23 Harbour Road, Wanchai, Hong Kong (CN).
- (21) International Application Number:
PCT/CN2003/000986
- (22) International Filing Date:
20 November 2003 (20.11.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant (for all designated States except US): GE MEDICAL SYSTEMS GLOBAL TECHNOLOGY COMPANY, LLC. [US/US]; 3000 North Grandview Boulevard-W-710, Waukesha, WI 53188 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): XU, Xiaodong [CN/CN]; No. 2 North Yong Chang Road, Beijing Economic & Technological Development Area, Beijing 100176 (CN).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: COLLIMATOR, X-RAY IRRADIATOR, AND X-RAY APPARATUS



(57) Abstract: A collimator is to be provided which permits the reduction of size without using any special material and without sacrificing an aperture. To this end, the collimator comprises: a pair of first plate members each having X-ray absorptivity, movable in a direction parallel to a surface thereof, and defining an X-ray passing aperture by a spacing between respective mutually opposed end faces; and a pair of second plate members each having X-ray absorptivity, the second block members, in order to block other X-rays than the X-ray passing through the aperture, being connected at respective one ends by hinges to end portions of the pair of first plate members opposite to the mutually opposed end faces of the first plate members and being supported at respective opposite ends so as to be movable obliquely with respect to the moving direction of the first plate members with movement of the first plate members.



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.